

### CV Series

Model	Capacity BTU/HR Watts		Dimensions						Inlet & Outlet Pipe Diameter in	Hp	KW	Pump GPM LPM		Reservoir		Rated Load Amps @460V	Minimum Circuit Ampacity @ 460V a	Approx. Weight (Dry)	
	65 Deg. F. LFT	18 Deg. C. LFT	Length in	cm	Width in	cm	Height in	cm				35 psi	2.38 bar	Gal	Liters			Lbs.	Kg.
2,000	22,000	6,448	36	91	26	66	52	132	1.25	0.75	0.56	10	38	24	91	6	8	400	182
3,000	39,000	11,430	50	127	28	71	62	157	1.25	0.75	0.56	18	68	40	151	8	11	730	331
5,000	70,500	20,600	50	127	28	71	62	157	1.25	0.75	0.56	18	68	40	151	11	16	830	377
7,500	100,000	29,200	58	147	32	81	67	170	1.5	1.5	1.12	36	132	70	265	17	24	935	425
10,000	121,000	35,400	58	147	32	81	67	170	1.5	1.5	1.12	35	132	70	265	23	30	975	443
12,000	158,000	46,307	58	147	42	107	86	218	1.5	2	1.49	40	151	100	379	28	39	1,105	502
15,000	190,000	55,686	58	147	42	107	86	218	1.5	2	1.49	40	151	100	379	31	44	1,225	557
20,000	237,000	69,461	75	191	42	107	86	218	2	3	2.24	60	303	120	464	39	62	1,900	864
25,000	311,000	90,000	100	254	42	107	86	218	2	3	2.24	80	303	180	681	52	80	2,100	955
30,000	341,000	99,800	100	254	42	107	86	218	2	3	2.24	80	303	180	681	57	100	2,300	1,045