



CW Series																				
Model	Capacity BTU/HR Watts		Dimensions						Pipe Diameter		Fluid	Cond.	Pump GPM	LPM	Reservoir		Rated Load Amps	Minimum Circuit Ampacity	Approx. Weight (Dry)	
	65 Deg. F. LFT	18 Deg C. LFT	Length		Width		Height		in	in					in	KW			35 psi	2.38 bar
1000	12,000	3,517	34	86	26	66	26	66	1	0.5	0.5	0.37	4	15	24	91	7(b)	8(b)	225	102
2000	24,000	7,034	36	91	26	66	47	119	1.25	0.75	0.75	0.56	10	38	24	91	5	7	400	182
3000	44,000	12,800	50	127	28	71	47	119	1.25	1	0.75	0.56	18	68	40	151	7	10	460	209
5000	73,000	21,300	50	127	28	71	47	119	1.25	1	0.75	0.56	18	68	40	151	9	16	830	377
7500	109,000	31,900	58	147	32	81	61	155	1.5	1.12	1.5	132	35	132	70	265	935	28	935	425
10,000	142,000	41,500	58	147	32	81	61	155	1.5	1.25	1.5	1.12	35	132	70	265	19	28	975	443
12,000	167,000	48,945	58	147	42	107	61	155	1.5	1.5	2	1.49	40	151	100	379	23	36	1,105	502
15,000	198,000	58,324	58	147	42	107	61	155	1.5	1.5	2	1.49	40	151	100	379	24	39	1,225	567
20,000	257,000	75,322	75	190	42	107	72	183	2	1.5	3	2.24	80	303	120	454	32	57	1,900	864
25,000	342,000	100,100	100	254	42	107	72	183	2	2	3	2.24	80	303	180	681	42	76	2,100	965
30,000	390,000	114,200	100	254	42	107	72	183	2	2	3	2.24	80	303	180	681	46	92	2,300	1,045
40,000	497,000	145,662	104	264	42	107	78	198	3	3	5	3.73	120	464	280	1060	65	106	2,550	1,159
50,000	627,000	183,763	104	264	42	107	78	198	3	3	5	3.73	150	568	280	1060	75	110	3,700	1,682
60,000	715,000	209,555	104	264	87	221	78	198	3	3	7.5	6.59	185	700	280	1060	94	122	3,800	1,727