



WV Series																			
Model	Capacity BTU/HR Watts		Dimensions						Fluid Pipe Dia.		Pump GPM LPM	Reservoir		Rated Load Amps	Minimum Circuit Ampacity	Approx. Weight (Dry)			
	65 Deg. F. LFT	18 Deg. C. LFT	Length		Width		Height		in	Hp		KW	35 psi			2.38 bar	Gal	Liters	@460V
1,000	11,000	3,224	32	81	20	51	39	99	0.75	0.33	0.25	4	15	12	45	17	19	500	227
2,000	23,000	6,741	36	91	26	64	58	147	1	0.6	0.37	10	38	18	68	5	8	750	341
3,000	38,000	11,137	50	127	28	71	75	191	1.25	1	0.75	15	57	18	68	9	12	900	409
6,000	70,500	20,600	56	140	28	71	76	191	1.25	1	0.75	15	57	42	159	12	16	1,200	645
7,500	100,000	29,300	58	147	32	81	80	203	1.25	1	0.75	22	83	42	159	16	24	1,600	727
10,000	121,000	26,400	58	147	32	81	80	203	1.5	1.6	1.12	30	114	42	159	23	30	2,000	909
12,000	160,000	46,899	58	147	42	107	99	251	1.5	1.5	1.12	36	136	82	310	27	39	2,300	1,045
15,000	191,000	56,979	58	147	42	107	99	251	2	1.6	1.12	45	170	82	310	31	41	2,400	1,091
20,000	240,000	70,340	100	254	42	107	98	249	2	2	1.49	60	227	120	454	38	60	2,500	1,136
25,000	311,000	90,000	100	254	42	107	98	249	2	2	1.49	75	284	120	454	61	79	2,800	1,273
30,000	341,000	99,800	100	254	42	107	98	249	3	3	2.24	90	341	120	454	57	100	3,200	1,455
40,000	462,000	135,404	75	191	87	221	88	224	3	5	3.73	120	454	120	454	81	116	3,800	1,727
50,000	590,000	172,919	104	264	87	221	88	224	3	5	3.73	150	568	220	833	97	125	4,800	2,182
60,000	681,000	199,590	104	264	87	221	88	224	3	7.6	5.69	180	681	220	833	118	138	5,200	2,364