



WW Series																						
Model	Capacity BTU/HR Watts		Dimensions						Pipe Diameter		Fluid	Cond.	Hp	KW	Pump GPM LPM		Reservoir		Rated Load Amps	Minimum Circuit Ampacity	Approx. Weight (Dry)	
	65 Deg. F. LFT	18 Deg C. LFT	Length		Width		Height		in	in					35 psi	2.38 bar	Gal	Liters	@460V	@ 460V a	Lbs.	Kg.
			in	cm	in	cm	in	cm														
1,000	12,000	3,517	44	112	30	76	44	112	0.75	0.5	0.33	0.25	4	15	12	45	12	14	500	227		
2,000	24,000	7,034	44	112	36	89	46	114	1	0.75	0.5	0.37	10	38	18	68	5	7	750	341		
3,000	43,000	12,600	50	127	35	89	50	127	1.25	1	1	0.75	15	57	18	68	7	11	900	409		
6,000	72,000	21,000	50	127	36	89	50	127	1.25	1.26	1	0.76	16	57	42	159	10	16	1,200	546		
7,500	109,000	31,900	57	145	40	102	65	165	1.25	1.25	1	0.75	22	83	42	159	13	22	1,600	727		
10,000	142,000	41,500	72	183	40	102	66	165	1.6	1.5	1.5	1.12	30	114	42	159	19	28	2,000	909		
12,000	169,000	49,531	72	183	40	102	65	165	1.5	1.5	1.5	1.12	36	136	82	310	23	35	2,300	1,045		
15,000	200,000	58,617	72	183	40	102	66	165	2	2	1.5	1.12	46	170	82	310	23	38	2,400	1,091		
20,000	260,000	76,202	72	183	52	132	75	191	2	2	2	1.49	60	227	120	454	31	55	2,500	1,136		
25,000	342,000	100,100	72	183	52	132	76	191	2	3	2	1.49	76	284	120	454	41	74	2,800	1,273		
30,000	348,000	116,500	72	183	52	132	75	191	3	3	3	2.24	90	341	120	454	46	92	3,200	1,455		
40,000	497,000	146,662	98	249	56	142	82	208	3	3	6	3.73	120	454	220	833	67	106	3,800	1,727		
50,000	627,000	183,763	108	274	56	142	82	208	3	3	5	3.73	150	568	220	833	78	110	4,800	2,182		
60,000	720,000	211,020	108	274	56	142	82	208	3	3	7.5	6.59	180	681	220	833	97	122	5,200	2,364		